


PROPELLER

15x9 2B E


PN: 2150900, 2150901



22 g
Mass



15.0"
Diameter



9.0"
Pitch



Fixed wing

Engine/Motor type: Electric

Rotation direction: Counter-clockwise and Clockwise available (Direction Guide)

Mass [g]: $22 \pm 12.0\%$

Moment of inertia [kgm^2]¹: $2.66\text{e-}04$

Core diameter [mm]: 13.1 (Drilling guide)

Limit RPM²: 12000

Working temperature [°C]: from -20°C to 60°C

Production method: Wet layup


¹ Moment of inertia is only an estimation: $I = \frac{1}{24} \cdot \text{mass} \cdot \text{diameter}^2 \cdot n^{\circ} \text{of blades}$

² RPM is limited by tip speed; forward speed reduces the limit.

For more information or custom propeller options, contact info@mejzlik.eu.
Operation manual: Propeller Maintenance and Repair Manual

Dynamic Performance Data

Simulated data - at 9300 RPM



v_inf	Ct	Cp	Propulsion efficiency	Advance ratio
0.0	0.1113	0.0424	0.0	0.0
5.0	0.1062	0.0442	0.203	0.0847
10.0	0.0995	0.045	0.3737	0.1693
15.0	0.0908	0.045	0.5112	0.254
20.0	0.0805	0.0439	0.6202	0.3387
25.0	0.0688	0.0413	0.703	0.4233
30.0	0.0558	0.0373	0.7578	0.508
35.0	0.0417	0.0313	0.7868	0.5927
40.0	0.0266	0.0235	0.7673	0.6773
45.0	0.0106	0.0141	0.5722	0.762
50.0	-0.0059	0.0054	-0.9266	0.8467
55.0	-0.0196	-0.0006	29.0639	0.9313

$$C_T = \frac{T}{\rho RPS^2 D^4}$$

$$C_P = \frac{P_{mech}}{\rho RPS^3 D^5}$$

$$\eta = \frac{C_T \cdot J}{C_P}$$

$$J = \frac{v_{inf}}{n \cdot D}$$