



PROPELLER

16x5.5 2B MC Folding

PN: 21600550, 21600551, 21600552, 21600553




37 g
Mass



9.6 kgf
Max Thrust



16.0"
Diameter



Multicopter



Engine/Motor type:	Electric
Rotation direction:	Counter-clockwise and Clockwise available (Direction Guide)
Features:	Folding Blades
Mass [g]:	37 ± 10.0%
Moment of inertia [kgm ²] ¹ :	5.09e-04
Center hole diameter [mm]:	4
Drilling pattern [mm]:	-
Limit hover RPM ² :	11200
Limit forward speed [m/s]:	Not calculated
Working temperature [°C]:	from -20°C to 60°C
Production method:	Wet layup

¹ Moment of inertia is only an estimation: $I = \frac{1}{24} \cdot mass \cdot diameter^2 \cdot n^{\circ} of blades$
² RPM is limited by tip speed; forward speed reduces the limit.

For more information or custom propeller options, contact info@mejzlik.eu.
Operation manual: Propeller Maintenance and Repair Manual

Static Performance Data

Simulated data



$$\text{Thrust (RPM): } 8.395e - 07 \cdot \text{RPM}^2 + -1.030e - 03 \cdot \text{RPM} + 1.205e + 00$$

$$\text{Torque (RPM): } 1.813e - 08 \cdot \text{RPM}^2 + -3.260e - 05 \cdot \text{RPM} + 4.502e - 02$$

$$\text{Mechanical power (RPM): } \frac{2\pi \cdot \text{Torque}[\text{Nm}] \cdot \text{RPM}}{60}$$

Formulas used to calculate FOM : $C_T = \frac{T}{\rho RPS^2 D^4}$ $C_P = \frac{P_{mech}}{\rho RPS^3 D^5}$ $FOM = \sqrt{\frac{2}{\pi} \frac{C_T^{3/2}}{C_P}}$